

Flexible, Reliable & Cost-effective Storage Expansion

Garantir GT-J3000 Series

Powered by PROMISE Technology



Features

- Expand Garantir GT R3000, A6000 and A7000 subsystems with Garantir GT-J3000 expansion units
- Industry leading performance and reliability at an excellent price
- Supports 12G/6GSAS and 6G SATA drives simultaneously
- Field replaceable SAS JBOD I/O modules
- 3U-16 form factor featuring hot-swappable drive bays
- Redundant power supplies
- Energy efficient system reduces power and cooling costs

Cost-effective Storage Expansion Platform

As the demands for capacity expansion explode for IT applications and video surveillance, it is imperative that IT administrators find a cost-effective way to meet performance and expansion goals. The Garantir GT-J3000 Series is a robust storage expansion platform that serves as a building block to provide reliability and flexibility in a cost-effective package that is simple to administer and meets the demands of your application. The 3U-16 bay Garantir GT-J3000 models are fully expandable to meet your needs today and in the future.

Redundant Power Supplies

The Garantir GT-J3000 Series is equipped with redundant power supplies. The advantage of power supplies is that should one fail, the other continues to power the subsystem until the faulty one can be replaced. Additionally, the power supplies are hot-swappable, which enables you to leave the subsystem running when you replace the one that failed.

Reduce Power and Cooling Costs

The Garantir GT-J3000 series utilize environmentally friendly production methods and materials as well as a high-efficiency design that saves energy. Sporting 80 Plus Gold Certified power supplies delivering up to 90% power efficiency, the Garantir GT-J3000 Series improves total cost of ownership by conserving power, reducing heat output and improving cooling costs.

Technical Specifications

Model and Number



Drive Support	<ul style="list-style-type: none"> Up to 16 3.5" drives 6/12GbSAS,6GbSATAHDDandSSD SupportsanymixofSASandSATA drivessimultaneouslyinthesameenclosure
External I/O Ports	Single (sS)/Dual (sD), IN/OUT 12G SAS-wide port over SFF-8644 per controller
Host Options	
SAS HBA	Follow Garantir GT-J3000 compatibility list
RAID Storage Subsystem	Garantir GT- R3000/GT- A6000/GT- A7000
SAS Features	
Expander Management Features	<ul style="list-style-type: none"> Self-configuring expander supports full SAS domain topology management EndDeviceFrameBuffering(aggregatebandwidththovertomultipleslowdevicee.g.6Gand3G) SmartcablesupporttodetectcabletypeandtunePHYautomaticallyformaximumreliability SMP-SAS Management Protocol In-band access to Expander and PHY information Statistic counters SESEM-SES Enclosure Management(ANSIT10SES2Compliant) SCSISES command set over virtual SSP device
System Management	
Management Interfaces	<ul style="list-style-type: none"> LEDstatusindicatorssupportfordrives,FRUandenclosureenvironmentals In-band SES enclosure management alerts user to out of spec operation: thermal condition, voltage condition or component failures, protecting data and hardware FullsubsystemmanagementCLIthroughout-of-bandRS232serialport
Enclosure Protocol and Management	ANSI T10 SES 2, SMP (SES over in-band SAS) VPD (Vital Product Data) on Chassis and FRUs
Mechanical Specifications	
Power Supply	CRPS 550W ;Efficiency 80PLUS Certified Redundant PSU
Voltage	AC: 100-240VAC; DC: 180-320VDC Auto-Ranging
Current	< 8A@100-240VAC@full load; < 8A@180-320VDC@full load
Power Conversion Efficiency	>80% @ 110V (>20% load), >80% @ 240V (>20% load) Temperature Range
Temperature Range	Operational: 5° to 35°C, Non-Operational: -40° to 60°C
Humidity	Operational: 20% to 80% (Non-Condensing), Non--Operational: ~ 95% (Non-Condensing)
Acoustic Noise Levels	<60dB, 25°C
Shock	Operational: 5G, 11 ms duration, Non-Operational: 30G, 11ms duration
Vibration	Operational: 0.2G, 5 to 500Hz (sine wave) ; 0.41G, 3-10-200-500Hz (Random) , Non-Operational: 1G, 5 to 500Hz (sine wave) ; 2.256G, 5-80-350-500Hz (Random)
Safety and Emission Certification	EMC Class A: CE, FCC, VCCI, BSMI, RCM Safety: IEEE CB, NTRL
Environmental Standards	RoHS, WEEE
Dimensions (H x W x D)	131mm x 446.7mm x 507mm (5.2" x 17.6" x 19.96")

Ver : 1.0

NOTE : Specifications are subject to change without notice. Garantir products referred to in this datasheet are trademarks of Garantir or its subsidiaries. All other trademarks belong to their respective owners.

As per Make in India initiative and Domestic Product value addition, GARANTIR & PROMISE is jointly working on the Storage range of Products in Indian market. All the Sales & Support activity taken care by Garantir Technologies Pvt. Limited.